



FINLAY 5032HD WHEELED CONVEYOR

FEATURES:-

- EP400 3-ply plain conveyor belt
- Heavy-duty main frame
- Radial axle
- Galvanised inner legs
- Extended feedboot
- Hydraulic motor*
- Ground level remote greasing system
- Hydraulic raise/lower cylinder*
- Quick couplings*
- Extended feedboot
- *Hydraulic coupled drive only

OPTIONS:-

- Electric drive
- Diesel hydraulic drive
- Chevron belt
- Hardox-lined feedboot
- Belt scales
- Overband magnet
- Metal detector
- Dust cover
- Dust suppression
- Hydraulic raise/lower handpump**
- ** Electric drive models only

ADVANTAGES

- Capable of handling up to 400TPH.
- Quick set up time typically under 20 minutes.
- High performance hydraulic system.

APPLICATIONS

- Sand and gravel
- Topsoil
- Coal
- Crushed stone



The Finlay wheeled stockpiling conveyors are designed for medium duty applications where stockpiling is required after a mobile or stationary crushing, screening or sand washing plant. This range has proven very popular due to its ease of operation and great value for money.

12m, 15m & 18m Standard Lengths Available
600mm, 750mm & 900mm Standard Widths Available
Hydraulic, Electric or Diesel Powered

sales@finlay.com.au - www.finlay.com.au



FINLAY 5032HD WHEELED CONVEYOR

Transport dimensions. L: 12.39m H: 3.081m W: 2.35m

