

C-1550+

CONE CRUSHER



Cone Head Diameter: 1300mm (52")

Net Engine Power: Tier 3/Stage IIIA:

Tier 4F:

Stage V:

Portability:

Tracked

Operating Weight: 50,250kg (110,782lbs) (Without options)

Caterpillar C15 403kW (540hp)

Scania DC13 405kW (550hp)

Scania DC13 405kW (550hp)

STRONG **HERITAGE**, STRONG **FUTURE**

 **FINLAY**[®]
A TEREX BRAND

SPECIFICATION

HOPPER / FEEDER

Hopper capacity: 6m³ (7.8yd³)

Feed height: 3.07m (10' 1")

Feed height with optional hopper extensions: 3.54m (11' 7")

Hopper fabricated in 10mm mild steel plate with combination of 10mm and 6mm wear resistant steel liners at impact point

Hopper Width at rear: 2.25m (7' 5")

Hopper Width at rear with optional hopper extensions: 4.1m (13' 5")

Belt Spec: Plain

Belt Width: 1.3m (51")

Speed range: variable, 0-32 m/min (0-105 ft/min)

Working Angle: 20°

Drive: Hydraulic variable speed drive via gearbox

Drop down rear door for auxiliary crusher feed

Crash bar fitted to reduce impact load on feed conveyor

Rubber covered impact rollers fitted

Hydraulic retraction system for ease of movement between transport and working modes

Tapered hopper and side barge boards to aid material flow

Full length skirting to head drum

Automatic variable speed conveyor ensures maximum output from plant

Metal detection system with 'auto-stop' feature is suitable for detecting steel and manganese steel contained in the feed material

Controllable discharge system to purge metal contaminants. This feature allows the operator to clear metal from the feed conveyor when it is detected. The contaminated material is dumped to the side of the machine. This can be done on the main control panel or remotely via the optional radio remote

CONE CHAMBER

Terex TC1300x 1300mm (52") cone chamber

Cone Counter Shaft Speed Range: 1342 - 1461 rpm

Variable speed control settings for producing a quality aggregate

Long throw fitted on standard configuration

Drive arrangement: Direct drive via clutch and v-belts

'On the fly' hydraulically adjustable closed side setting with monitoring system

Mantle/concave wear indicator

Hydraulic overload protection with automatic reset. This allows the upper frame to lift up, to permit the passage of tramp iron and other un-crushable material. The system then automatically returns the upper frame to its original position

Unrestricted feed opening reduces blockages, bridging and maximizes output



Hopper and Feeder



Hopper and Feeder



Cone Chamber



Cone Chamber

Concave	Maximum Feed Size	Recommended CSS Range
Medium Coarse	220mm (8 11/16")	20-50mm (13/16" – 1 15/16")

CONE CHAMBER continued

Independent cone oil lubrication tank with separate oil cooler

Level sensor fitted over inlet feed box maintains the optimum choke feed condition hence maximizing the reduction and manganese life

Dust suppression fitted at cone outlet

MAIN CONVEYOR

Belt Width: 1.1m (44")

Belt Spec: Plain

Working Angle: 23°

Speed: 105 – 120 m/min (344 – 393 ft/min)

Discharge Height: 3.6m (11' 10")

Impact bars and wear resistant liners at feed point

High spec scraper at head drum

Dust suppression: fitted with hose and spray nozzles as standard (no pump supplied)

Full length skirting to head drum

Dust covers (Optional)

Stockpile level sensor (Optional)

Stockpile capacity: 69m³ (90yds³)

POWERPACK

Tier 3 / Stage IIIA : Caterpillar C15

Engine Power: 403kW (540hp)

Engine Speed : 1700 - 1850 rpm

Tier 4F: Scania DC13

Engine Power: 405kW (550hp)

Engine Speed: 1700 - 1850 rpm

Stage V: Scania DC13

Engine Power: 405kW (550hp)

Engine Speed: 1700 - 1850 rpm

TANK CAPACITIES

Hydraulic Tank: 660 litres / 145 UK gal / 174 US gal

Fuel Tank: 1000 litres / 220 UK gal / 264 US gal

Urea Tank: 60 litres / 13 UK gal / 15 US gal

UNDERCARRIAGE

Shoe Width: 500mm (20")

Sprocket Centres: 3.80m (12' 6")

Tracking Speed: 1.2 km/h

Gradeability: 25°



Main Conveyor - shown with optional dust covers



Powerunit (Scania)



Undercarriage

TOOL BOX

Mounted lockable toolbox

Tool kit supplied

Two grease guns supplied – one for machine, one for cone

CHUTES

Quick release cone feed box for cone wear part changes

Cone chamber feed box fabricated in 6mm mild steel plate

Cone chamber discharge chute fabricated in 10mm mild steel plate with 10mm wear resistant steel liners at impact point

Contamination chute fabricated in 5mm mild steel plate

CONTROL SYSTEM

Advanced CANBUS compliant system

Large colour display screen

Main menu consists of five modes:

Automatic mode: For automatically starting the machine in a set sequence

Track mode: For moving machine

Setup mode: For folding / setting up machine

Cone setup mode: For testing / setting of cone

Configuration mode: For testing / setting individual components / monitoring engine performance and faults / monitoring machine faults

User friendly incremental selection of feeder and engine speed, enable the operator to achieve the optimal throughput and product shape

The main control panel is mounted to the side of the machine in a lockable compartment

PLATFORMS

Galvanised catwalks and ladders for full maintenance and service access

Catwalks on both sides of the machine

Compact folding for transport

REMOTE CONTROL UNIT

Full function radio remote unit:

- Auto start / stop
- Feed conveyor start / stop
- Adjust feed conveyor speed
- Adjust engine rpm
- Metal purge sequence
- Tracking



Chutes



Platforms

STANDARD FEATURES

ENGINE:

Tier 3 / Stage IIIA - Caterpillar C15 328kW (440hp)

Tier 4 Final:- Scania DC13 405kW (550hp)

Stage V: Scania DC13 405kW (550hp)

CONE CHAMBER:

Terex TC1300X

Medium coarse concave (max feed size 220mm)

Direct drive via clutch

HOPPER / FEEDER:

Fixed hopper c/w wear resistant liner plates

Belt width: 1.3m (51")

Metal detector & Metal contaminants purge system

MAIN CONVEYOR:

Belt width: 1.1m (44")

Dust covers

CLIMATE SPEC:

Standard oils (Recommended for ambient temperatures between -5 to +30°C)

DUST SUPPRESSION:

Piped for dust suppression c/w spraybars

ELECTRICAL:

Emergency stops

Hand held track control set with connection lead

T-Link Telemetry System fitted c/w 7 years data subscription

Radio remote system

GENERAL:

Safety guards in compliance to machinery directive

One auxiliary drive

OPTIONAL EQUIPMENT

Sand concave - max feed size 63mm (check leadtime) ¹

Camera & Viewing screen

Hydraulic hopper extensions

Belt weigher

Stockpile level sensor

Hot climate lubrication kit (Recommended for ambient temperatures between +15 to +50°C)

Cold climate lubrication kit (Recommended for ambient temperatures between -20 to +30°C)

Hydraulic driven water pump

Lighting mast



Hopper / Feeder

- ▲ Hopper capacity: 6m³ (7.8yd³)
- ▲ Feed height: 3.07m (10' 1")
- ▲ Feed height with optional hopper extensions: 3.54m (11' 7")
- ▲ Hopper Width at rear: 2.25m (7' 5")
- ▲ Hopper Width at rear with optional hopper extensions: 4.1m (13' 6")
- ▲ Belt Spec: Plain
- ▲ Belt Width: 1.3m (51")
- ▲ Speed range: variable, 0-32 m/min (0-105 ft/min)
- ▲ Working Angle: 20°

Platforms

- ▲ Galvanised catwalks and ladders for full maintenance and service access
- ▲ Catwalks on both sides of the machine
- ▲ Compact folding for transport

Powerpack

- ▲ Tier 3 / Stage IIIA : Caterpillar C15
Engine Power: 403kW (540hp)
Engine Speed : 1700 - 1850 rpm
- ▲ Tier 4F: Scania DC13
Engine Power: 405kW (550hp)
Engine Speed: 1700 - 1850 rpm
- ▲ Stage V: Scania DC13
Engine Power: 405kW (550hp)
Engine Speed: 1700 - 1850 rpm

Main conveyor

- ▲ Belt Width: 1.1m (44")
- ▲ Belt Spec: Plain
- ▲ Speed: 105 – 120 m/min (344 – 393 ft/min)
- ▲ Discharge Height: 3.6m (11' 10")

Metal purge system

- ▲ Metal purge chute standard

Cone chamber

- ▲ Terex TC1300x 1300mm (52") cone chamber
- ▲ Cone Counter Shaft Speed Range: 1342 - 1461 rpm
- ▲ Variable speed control settings for producing a quality aggregate
- ▲ Drive arrangement: Direct drive via clutch and v-belts
- ▲ 'On the fly' hydraulically adjustable closed side setting with monitoring system
- ▲ Mantle/concave wear indicator

Undercarriage

- ▲ Shoe Width: 500mm (20")
- ▲ Sprocket Centres: 3.80m (12' 6")
- ▲ Tracking Speed: 1.1 km/h
- ▲ Gradeability: 25°

TRANSPORT DIMENSIONS



WORKING DIMENSIONS



Note: Images and dims above are for standard plant (no options)

MACHINE WEIGHT: 50,250kg (110,782lbs)
without options
51,700kg (113,979lbs)
with optional hopper extensions and main conveyor dust covers

For further information on specific machine weight configurations please consult Terex Finlay